



Artikel-Nr. GTIN 4003984	Abmessungen mm			Stärke	Lochzahl	ca. kg je VE	verp. zu	CE Kennzeichnung	Verpackungsart
	A	B	C						
071060025 213950	102	25	-	1,0	-	0,44	20	CE	-
071060038 213967	127	38	-	1,0	-	0,81	20	CE	-

Nagelplatten sendzimir verzinkt




070946000 ¹⁾ 210379	30	30	170	2,0	10	4,81	50	CE	-
070947000 ²⁾ 210386	30	30	170	2,0	10	4,78	50	CE	-
070948000 ¹⁾ 210393	30	30	210	2,0	26	6,83	50	CE	-
070949000 ²⁾ 210409	30	30	210	2,0	26	6,73	50	CE	-
070950000 ¹⁾ 210416	30	30	250	2,0	34	8,43	50	CE	-
070951000 ²⁾ 210423	30	30	250	2,0	34	8,43	50	CE	-
070946000G ¹⁾ 212274	30	30	170	2,0	10	1,87	1à20	CE	
070947000G ²⁾ 212281	30	30	170	2,0	10	1,97	1à20	CE	
070948000G ¹⁾ 212298	30	30	210	2,0	26	2,59	1à20	CE	
070949000G ²⁾ 212304	30	30	210	2,0	26	2,56	1à20	CE	
070946000HP ¹⁾ 668514	30	30	170	2,0	10	4,76	1à50	CE	
070947000HP ²⁾ 668521	30	30	170	2,0	10	4,77	1à50	CE	
070946000RF ¹⁾ 380126	30	30	170	2,0	10	0,97	10	CE	-
070947000RF ²⁾ 380133	30	30	170	2,0	10	1,00	10	CE	-

¹⁾ = (rechts)
²⁾ = (links)



Abb. links

Sparrenpfettenanker sendzimir verzinkt



RF = V4A

070958000 212106	36	36	170	2,0	9	4,38	50	CE	-
070959000 212113	36	36	210	2,0	13	5,67	50	CE	-

Universal-Pfettenanker werden als Verbinder von kreuzenden Hölzern eingesetzt und können sowohl **links als auch rechts** angeschlagen werden.


Vorteile:

- rechts und links verwendbar
- schnell fixierbar durch Montagedorne
- für jede Sparrenneigung
- durch amtliche Typenprüfung abgesichert
- geprüft auch für Teilausnagelung
- Kennzeichnung als geregeltes Bauprodukt
- platzsparende Lagerhaltung




Universal-Sparrenpfettenanker rechts = links

sendzimir verzinkt



070968025 212557	-	25	78	1,0	12	2,02	25	-	-
070968038 212564	-	38	72	1,0	12	1,91	25	-	-
070968040 212571	-	40	70	1,0	12	2,02	25	-	-
070968046 212588	-	46	66	1,0	12	2,02	25	-	-
070968050 212595	-	50	63	1,0	12	2,02	25	-	-
070968059 212601	-	59	69	1,0	12	2,58	25	-	-



Leichte Balkenschuhe sendzimir verzinkt

